

SAMSUNG

High Quality

16CH/8CH H.264 DVR



16CH/8CH CIF Real-time H.264 Digital Video Recorder

SRD-1652D/852D

- 16CH/8CH real-time DVR
- Video (H.264) / Audio (ADPCM)
- Up to 480 (NTSC) / 400 (PAL)fps recording rate : SRD-1652D
240 (NTSC) / 200 (PAL)fps recording rate : SRD-852D
- Up to 16CH audio inputs and 1CH audio output : SRD-1652D
8CH audio inputs and 1CH audio output : SRD-852D
- Combined BNC and VGA video output for main display
- Max 4 internal HDD (HDD x 4)
- HDD & DVD SATA interface, DDNS
- Support for smart phone(Android, i-Phone)
- Built-in DVD-RW

16CH/8CH CIF Real-time H.264 Digital Video Recorder

SRD-1652D/852D




SRD-1652D



SRD-852D

Dimensions

Unit : mm (inch)



Specifications

		SRD-1652D	SRD-852D
DISPLAY			
Video	Inputs	16 Composite video 0.5-1 Vp-p	8 Composite video 0.5-1 Vpp
	Resolution	NTSC : 704 x 480 / PAL : 704 x 576	
	Frame Rate	NTSC : 480fps / PAL : 400fps	NTSC : 240fps / PAL : 200fps
Live	Resolution	NTSC : 704 x 480 / PAL : 704 x 576	
	Multi Screen Display	1 / 4 / 6 / 8 / 9 / 13 / 16 / PIP	1 / 4 / 6 / 8 / 9 / 13 / PIP
PERFORMANCE			
Operating System	Embedded	Linux	
	Compression	H.264	
Recording	Record Rate	NTSC : Up to 120fps@704 x 480 NTSC : Up to 240fps@704 x 240 NTSC : Up to 480fps@352 x 240	NTSC : Up to 60fps@704 x 480 NTSC : Up to 120fps@704 x 240 NTSC : Up to 240fps@352 x 240
		PAL : Up to 100fps@704 x 576 PAL : Up to 200fps@704 x 288 PAL : Up to 400fps@352 x 288	PAL : Up to 50fps@704 x 576 PAL : Up to 100fps@704 x 288 PAL : Up to 200fps@352 x 288
		Mode	NTSC : Manual, Schedule (Continuous / Event), Event (Pre / Post), Time lapse (0.9 / 1.9 / 3.8 / 7.5 / 15 / 30fps) PAL : Manual, Schedule (Continuous / Event), Event (Pre / Post), Time lapse (0.8 / 1.6 / 3.1 / 6.2 / 12.5 / 25fps)
	Overwrite Modes	Continuous	
Search & Playback	Pre-alarm	Up to 5sec	
	Post-alarm	Up to 6hour (5,10, 20, 30sec, 1, 3, 5, 10, 20min, 1, 2, 3, 4, 5, 6hour)	
	Search Mode	Date/Time, Event, Back up, Pos, Motion (*All search mode include preview function)	
Network	Playback Function	Fast forward / backward, Slow forward / backward, Step forward / backward	
	Transmission Speed	CIF 120/100fps	
	Bandwidth	Up to 8Mbps, Unlimited (8M) / 2 / 1.5 / 1Mbps / 800 / 600 / 500 / 400 / 300 / 200 / 100 / 50kbps	
	Bandwidth Control	Selectable	
Smart Phone	Stream	H.264 (4CIF / 2CIF / CIF selectable)	
	Max. Remote Users	Search 3 / Live unicast 10 / Live multicast 20	
	Protocol Support	TCP/IP, DHCP, PPPoE, SMTP, NTP, HTTP, DDNS, RTP, RTSP	
	Monitoring	NET-i viewer, SmartViewer, Webviewer	
Storage	Smart Phone	Android, i-Phone	
	Protocol Support	RTSP/RTP (UDP), CGI, HTTP	
	Transmission Speed	Wi-Fi : CIF Max. 4fps (Single channel) / CIF Max. 4fps (Quad channel) 3G : CIF Max. 4fps (Single channel) / CIF Max. 4fps (Quad channel)	
Security	Max. Remote Users	Live 1	
	Internal HDD	Up to 4 SATA HDDs	
	DVD Writer (Back up)	Yes	
INTERFACE	USB (Back up)	2 USB ports	
	File Format (Back up)	AVI, BU (DVR player), EXE (Include player)	
Monitors	Password Protection	1 Admin, 10 Group, 20 User per 1 group, User can be assigned authority for function	
	Data Authentication	Watermark	
Audio	VGA	1 VGA (800 x 600, 1024 x 768, 1280 x 1024)	
	Main Composite	1 BNC, 1.0 Vp-p, 75 ohm	
	Spot Composite	Analogue spot (1 BNC, 1 Vp-p, 75 ohm)	
Alarm	Inputs / Output	4 Line in (Built-in 4CH, RCA / 1CH line out (RCA))	
	Compression	ADPCM	
Connections	Sampling Rate	16KHz	
	Remote Notification	Terminal 16 inputs (NO/NC), Terminal 1 inputs (Alarm Reset), Terminal 4 relay outputs (NO/NC), Rating : 24V DC / 1A, 125V AC / 0.5A	Terminal 8 inputs (NO/NC), Terminal 1 inputs (Alarm Reset), Terminal 4 relay outputs (NO/NC), Rating : 24V DC / 1A, 125V AC / 0.5A
	Ethernet	Notification via e-mail	
	Serial Interface	1 RJ-45 10/100/1000 Base-T	
GENERAL	Serial Interface	RS-232/RS-485 for PTZ, Samsung system keyboard	
	USB	USB 2.0, 2 ports (Front)	
	Application Support	Mouse, Remote controller	
Electrical	Protocol Support	Samsung-T/E, Pelco-D/P, Panasonic, Phillips, AD, DIAMOND, ERNA, KALATEL, VCL TP, Vicon	
	Input Voltage / Current	100 ~ 240V AC ±10%, 50/60Hz, Autoranging	
Environmental	Power Consumption	Max. 60W (With 1x HDD)	
	Operating Temperature / Humidity	+0°C ~ +40°C (+32°F ~ +104°F) / 20% ~ 85% RH	
Mechanical	Dimensions (WxHxD)	440.0 x 88.0 x 426.8mm (17.32" x 3.46" x 16.80")	
	Weight (With hard disks)	Approx. 7.5Kg (16.53 lb)	
Language	Rack Mount Kit	2ea	
		Korean, Japanese, Chinese, English, French, German, Spanish, Italian, Russian, Polish, Czech, Turkish, Netherlands, Portuguese, Swedish, Danish, Thai, Rumanian, Serbian, Croatian, Hungarian, Greek (22 Language)	



The Eco mark represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.

Design and specifications are subject to change without notice.



SAMSUNG TECHWIN CO., LTD.

701, Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do Korea 463-440
Tel : +82-70-7147-8741 ~ 8749, 8752 ~ 8760 Fax : +82-31-8018-3745
www.samsungsecurity.com www.samsungcctv.com

SAMSUNG TECHWIN AMERICA Inc.

100 Challenger Rd. Suite 700 Ridgely Park, NJ 07660
Toll Free : +1-877-213-1222 Direct : +1-201-325-6920
Fax : +1-201-373-0124
www.samsungcctvusa.com

SAMSUNG TECHWIN EUROPE LTD.

Samsung House, 1000 Hillwood Drive, Hillwood Business Park
Chertsey, Surrey, UNITED KINGDOM KT16 0PS
Tel : +44-1932-45-5300 Fax : +44-1932-45-5325

TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONICS CO., LTD.

No.11 Wei 6 Street, Micro-Electronic Industrial Park
Jingang Road, Tianjin, P.R. CHINA 300385
Tel : +86-22-23887788 Fax : +86-22-23887788

■ DISTRIBUTED BY

